

LOW PROFILE SCOOP RAKE



A DIVISION OF LIFCO

- Features an extra wide body with close tines. These are used after all the large rocks and big stumps have been removed. They work great to get all the loose roots and smaller rocks out, leaving you with a nice landscaped finish.
- Constructed from Canada and USA made T1 & AR400 Steel at all critical points.
- Thick shanks support themselves without gussets.
- Standard screening gap is 6 inches. We do custom sizes between 4" and 8" as well, please call for custom quote.
- Heavy Duty Low Profile ScoopRakes are not designed for extreme applications (eg. Deep penetration in hard ground, ripping out large stumps and rocks, etc.). Please inquire about our Severe Duty Scoop Rakes.



CLICK TO CHECK AVAILABILITY & PRICING

Machine Class	Product Code	Tines	Width	Shank Thickness	Rake Height	Approx. Weight (Lbs)
8-11 Ton	LPSR-008-011-W048T08	8	48"	0.75"	20"	536
	LPSR-008-011-W060T09	9	60"			626
	LPSR-008-011-W072T11	11	72"			749
12-16 Ton	LPSR-012-016-W060T09	9	60"	1.00"	22"	982
	LPSR-012-016-W072T11	11	72"			1173
	LPSR-012-016-W084T12	12	84"			1308
17-21 Ton	LPSR-017-021-W060T09	9	60"	1.25"	25"	1354
	LPSR-017-021-W072T10	10	72"			1537
	LPSR-017-021-W084T12	12	84"			1805
22-27 Ton	LPSR-022-027-W060T09	9	60"	1.25"	28"	1670
	LPSR-022-027-W072T10	10	72"			1886
	LPSR-022-027-W084T12	12	84"			2210
28-35 Ton	LPSR-028-035-W072T10	10	72"	1.50"	32"	2544
	LPSR-028-035-W084T12	12	84"			2979
	LPSR-028-035-W096T13	13	96"			3260
36-44 Ton	LPSR-036-044-W084T11	11	84"	1.75"	36"	4140
	LPSR-036-044-W096T13	13	96"			4802
	LPSR-036-044-W108T14	14	108"			5213
45-55 Ton	LPSR-045-055-W096T12	12	96"	2.00"	40"	6025
	LPSR-045-055-W108T14	14	108"			6899
	LPSR-045-055-W120T15	15	120"			7444

Pins sold separately. Wedge Style Ears: Available (Non-standard only).

1-800-952-7849

trkattachments.com

trk@trkattachments.com

All attachments include a 1 year limited warranty. If you have any questions or have a custom requirement for your attachment, please give us a call.