

SABRE TOOTH STUMP AND ROOT RIPPER

LIFCO
HYDRAULICS & ATTACHMENTS

- AR400 wear plates on sides.
- AR400 Sabre Teeth on front.
- Rock Chisel Tooth installed.
- Longer Shank for deeper penetration.
- Double Shank Ripper also available (please inquire).

Machine Class	Product Code	Shank Thickness	Length*	Tooth Type	Approx. Weight (Lbs)
04-07 Ton	STSR-030-04-07	2.25"	30"	J250	332
08-11 Ton	STSR-036-08-11	2.50"	36"	J300	470
12-22 Ton	STSR-042-12-22	2.00"	42"	J350	988
23-33 Ton	STSR-048-23-33	2.50"	48"	J400	1376
34-45 Ton	STSR-054-34-45	3.00"	54"	J450	1855
46-55 Ton	STSR-060-46-55	3.50"	60"	J550	2756



VIDEO 1

VIDEO 2

SEVERE DUTY ROCK RIPPER AND FROST PICK

- AR400 wear plates on sides, front edge and back.
- Oversized Rock Chisel Tooth installed.
- Extra Thick Shank.

Machine Class	Product Code	Shank Thickness	Length*	Tooth Type	Approx. Weight (Lbs)
04-07 Ton	SDRR-018-04-07	2.50"	18"	J250	289
08-11 Ton	SDRR-024-08-11	3.00"	24"	J300	425
12-22 Ton	SDRR-030-12-22	2.50"	30"	J350	875
23-33 Ton	SDRR-036-23-33	3.00"	36"	J400	1220
34-45 Ton	SDRR-042-34-45	3.50"	42"	J450	1770
46-55 Ton	SDRR-048-46-55	4.00"	48"	J550	2590

Pins sold separately. Wedge Style Ears: (Non-standard Only) Available.

*Length is measured from the bottom of the base to tip of tooth.



1-800-952-7849

lifcohydraulics.com

sales@lifcoattachments.com

All attachments include a 1 year limited warranty. If you have any questions or have a custom requirement for your attachment, please give us a call.