

# LOW PROFILE SCOOP RAKE **LIFCO**

**HYDRAULICS & ATTACHMENTS**

- Features an extra wide body with close tines. These are used after all the large rocks and big stumps have been removed. They work great to get all the loose roots and smaller rocks out, leaving you with a nice landscaped finish.
- Constructed from Canada and USA made T1 & AR400 Steel at all critical points.
- Thick shanks support themselves without gussets.
- Standard screening gap is 6 inches. We do custom sizes between 4" and 8" as well, please call for custom quote.
- Heavy Duty Low Profile ScoopRakes are not designed for extreme applications (eg. Deep penetration in hard ground, ripping out large stumps and rocks, etc.). Please inquire about our Severe Duty Scoop Rakes.

**CLICK TO CHECK AVAILABILITY & PRICING**



Machine Class	Product Code	Tines	Width	Shank Thickness	Rake Height	Approx. Weight (Lbs)
8-11 Ton	LPSR-048-08-11-08	8	48"	0.75"	20"	536
	LPSR-060-08-11-09	9	60"			626
	LPSR-072-08-11-11	11	72"			749
12-16 Ton	LPSR-060-12-16-09	9	60"	1.00"	22"	982
	LPSR-072-12-16-11	11	72"			1173
	LPSR-084-12-16-12	12	84"			1308
17-21 Ton	LPSR-060-17-21-09	9	60"	1.25"	25"	1354
	LPSR-072-17-21-10	10	72"			1537
	LPSR-084-17-21-12	12	84"			1805
22-27 Ton	LPSR-060-22-27-09	9	60"	1.25"	28"	1670
	LPSR-072-22-27-10	10	72"			1886
	LPSR-084-22-27-12	12	84"			2210
28-35 Ton	LPSR-072-28-35-10	10	72"	1.50"	32"	2544
	LPSR-084-28-35-12	12	84"			2979
	LPSR-096-28-35-13	13	96"			3260
36-44 Ton	LPSR-084-36-44-11	11	84"	1.75"	36"	4140
	LPSR-096-36-44-13	13	96"			4802
	LPSR-108-36-44-14	14	108"			5213
45-55 Ton	LPSR-096-45-55-12	12	96"	2.00"	40"	6025
	LPSR-108-45-55-14	14	108"			6899
	LPSR-120-45-55-15	15	120"			7444

Pins sold separately. Wedge Style Ears: Available (Non-standard only).

**1-800-952-7849**

**lifcohydraulics.com**

**sales@lifcoattachments.com**

All attachments include a 1 year limited warranty. If you have any questions or have a custom requirement for your attachment, please give us a call.