

LOW PROFILE RAKE

LIFCO
HYDRAULICS & ATTACHMENTS

- Features an extra wide body with close tines. These are used after all the large rocks and big stumps have been removed. They work great to get all the loose roots and smaller rocks out, leaving you with a nice landscaped finish.
- Constructed from Canada and USA made T1 & AR400 Steel at all critical points.
- Thick shanks support themselves without gussets.
- Standard screening gap is 6 inches. We do custom sizes between 4" and 8" as well, please call for custom quote.
- Heavy Duty Low Profile Rakes are not designed for extreme applications (eg. Deep penetration in hard ground, ripping out large stumps and rocks, etc.). Please inquire about our Severe Duty Low Profile Rakes.



Machine Class	Product Code	Width	Shank Thickness	Rake Height	Approx. Weight (Lbs)
8-11 Ton	LPR-048-08-11-6	48"	0.75"	14"	489
	LPR-060-08-11-6	60"			550
	LPR-072-08-11-6	72"			648
12-16 Ton	LPR-060-12-16-6	60"	1.00"	15"	853
	LPR-072-12-16-6	72"			1003
	LPR-084-12-16-6	84"			1099
17-21 Ton	LPR-060-17-21-6	60"	1.25"	16"	1139
	LPR-072-17-21-6	72"			1261
	LPR-084-17-21-6	84"			1463
22-27 Ton	LPR-060-22-27-6	60"	1.25"	17"	1326
	LPR-072-22-27-6	72"			1462
	LPR-084-22-27-6	84"			1689
28-35 Ton	LPR-072-28-35-6	72"	1.50"	18"	2173
	LPR-084-28-35-6	84"			2505
	LPR-096-28-35-6	96"			2706
36-44 Ton	LPR-084-36-44-6	84"	1.75"	19"	2749
	LPR-096-36-44-6	96"			3141
	LPR-108-36-44-6	108"			3373
45-55 Ton	LPR-096-45-55-6	96"	2.00"	20"	3942
	LPR-108-45-55-6	108"			4454
	LPR-120-45-55-6	120"			4752

Pins sold separately. Wedge Style Ears: Available (Non-standard patterns, additional charges may apply).

1-800-952-7849
lifcohydraulics.com
sales@lifcoattachments.com

All attachments include a 1 year limited warranty. If you have any questions or have a custom requirement for your attachment, please give us a call.